

Sensira FTXC

Zidna jedinica | Hlađenje i grijanje



FTXC-E





RXC-E



ARC486A2



uključeno*



Cijene		FTXC20E + RXC20E	FTXC25E + RXC25E	FTXC35E + RXC35E	FTXC50E + RXC50E	FTXC60E + RXC60E	FTXC71E + RXC71E
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	€ 775,-	€ 837,50	€ 887,50	€ 1.337,50	€ 1.612,-	€ 2.200,-
	Cijena unutarnje jedinice	€ 262,50	€ 287,50	€ 300,-	€ 450,-	€ 537,50	€ 737,50
	Cijena vanjske jedinice	€ 512,50	€ 550,-	€ 587,50	€ 887,50	€ 1.075,-	€ 1.462,50
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	€ 620,-	€ 670,-	€ 710,-	€ 1.070,-	€ 1.290,-	€ 1.760,-
	Cijena unutarnje jedinice	€ 210,-	€ 230,-	€ 240,-	€ 360,-	€ 430,-	€ 590,-
	Cijena vanjske jedinice	€ 410,-	€ 440,-	€ 470,-	€ 710,-	€ 860,-	€ 1.170,-

Energetska učinkovitost			FTXC20E + RXC20E	FTXC25E + RXC25E	FTXC35E + RXC35E	FTXC50E + RXC50E	FTXC60E + RXC60E	FTXC71E + RXC71E
Rashladni učin	Min./Rated/Max.	kW	1,3/2,0/3,0	1,3/2,5/3,0	1,3/3,5/4,0	1,4/5,1/6,2	1,8/6,2/7,0	2,3/7,1/7,3
Učin grijanja	Min./Rated/Max.	kW	1,3/2,5/4,0	1,3/2,8/4,0	1,3/4,0/4,8	1,4/5,6/6,6	1,5/6,4/8,0	2,3/8,0/9,0
Prikjučna snaga	Hlađenje	Min./Nom./Max.	kW	0,30/0,60/1,15	0,30/0,77/1,15	0,32/1,05/1,74	0,30/1,55/2,11	0,38/1,89/2,05
	Grijanje	Min./Nom./Max.	kW	0,28/0,67/1,35	0,28/0,75/1,35	0,28/1,07/1,57	0,27/1,52/1,85	0,33/1,68/2,35
Hlađenje	Oznaka energetske učinkovitosti		A ⁺⁺ (D->A ⁺⁺⁺)					
	Učin	Pdesign	kW	2,08	2,57	3,44	5,08	6,21
	SEER			6,89	6,84	6,87	6,45	6,40
	Godišnja potrošnja energije		kWh/a	106	131	175	276	339
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti		A ⁺ (D->A ⁺⁺⁺)					
	Učin	Pdesign	kW	1,87	2,23	2,24	3,90	4,10
	SCOP/A			4,40	4,45	4,28	4,42	4,24

Unutarnja jedinica				FTXC20E	FTXC25E	FTXC35E	FTXC50E	FTXC60E	FTXC71E
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	288x770x234			297x990x273		
Kvaliteta zraka				Filtar od titanijeva apatita, filtar za zrak					
Ventilator - brzina protoka zraka	Hlađenje	Tihi/Niski/Srednji/Visoki	m ³ /min	5,4/6,1/8,1/10,8		5,4/6,4/8,7/11,1	7,4/8,2/9,9/12,5	10,2/12,5/14,5/20,4	
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dB(A)	21/26/33/40		22/26/34/41	30/33/39/47	31/38/42/48	

Vanjska jedinica				RXC20E	RXC25E	RXC35E	RXC50E	RXC60E	RXC71E
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	550x658x273			615x845x300		695x930x350
Razina zvučnog tlaka	Hlađenje	Visoki	dB(A)	45		46	51	54	
Radno područje	Hlađenje	Okolina	Min.-Max.	10~46			-10~46		
	Grijanje	Okolina	Min.-Max.	-15~24					
Radna tvar	Tip / GWP / Punjenje		kg/TCO _{Eq}	R-32/675/0,55/0,371		R-32/675/0,75/0,506	R-32/675/1,00/0,675	R-32/675/1,10/0,743	R-32/675/1,15/0,776
Dimenzije priključka	Duljina cijevi	VJ - UJ	Max.	20			30		
	Sustav	Prednapunjeno					8		
	Visinska razlika	UJ - VJ	Max.	15			20		
Napajanje	Faza / Preporučeni osigurač (MFA)		A				1~/16		

Standardni infracrveni bežični daljinski upravljač uključen u isporuku.

Daikin Hrvatska d.o.o.

Strojarska cesta 20, 10 000 Zagreb, Hrvatska | Tel.: + 385 1 60 65 850 | e-mail: office@daikin.hr | www.daikin.hr