

Sensira FTXF

Zidna jedinica | Hlađenje i grijanje



FTXF-E





RXF-E



ARC470A1



BRP069B45/BRP069C47*



Učinkovitost	Rad	Pročišćavanje zraka	Protok zraka	Upravljanje i određivanje rasporeda	Ostalo
				opcija	

Cijene		FTXF20F + RXF20F	FTXF25F + RXF25F	FTXF35F + RXF35F	FTXF42F + RXF42F	FTXF50F + RXF50F	FTXF60F + RXF60D9	FTXF71F + RXF71D9
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	€ 850,-	€ 912,50	€ 975,-	€ 1.162,50	€ 1.462,50	€ 1.762,50	€ 2.362,50
	Cijena unutarnje jedinice	€ 287,50	€ 300,-	€ 325,-	€ 387,50	€ 487,50	€ 587,50	€ 787,50
	Cijena vanjske jedinice	€ 562,50	€ 612,50	€ 650,-	€ 775,-	€ 975,-	€ 1.175,-	€ 1.575,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	€ 680,-	€ 730,-	€ 780,-	€ 930,-	€ 1.170,-	€ 1.410,-	€ 1.890,-
	Cijena unutarnje jedinice	€ 230,-	€ 240,-	€ 260,-	€ 310,-	€ 390,-	€ 470,-	€ 630,-
	Cijena vanjske jedinice	€ 450,-	€ 490,-	€ 520,-	€ 620,-	€ 780,-	€ 940,-	€ 1.260,-

Energetska učinkovitost		FTXF20F + RXF20F	FTXF25F + RXF25F	FTXF35F + RXF35F	FTXF42F + RXF42F	FTXF50F + RXF50F	FTXF60F + RXF60D9	FTXF71F + RXF71D9	
Rashladni učin	Min./Nom./Max.	kW 1,3/2,0/2,4	kW 1,3/2,5/2,8	kW 1,3/3,3/3,8	kW 1,4/4,2/4,3	kW 1,3/5,0/5,3	kW 1,7/6,0/7,0	kW 2,3/7,1/7,3	
Učin grijanja	Min./Nom./Max.	kW 1,3/2,4/3,3	kW 1,3/2,8/3,7	kW 1,3/3,5/4,4	kW 1,4/4,6/5,0	kW 1,4/5,4/6,1	kW 1,7/6,4/8,0	kW 2,3/8,2/9,0	
Prikjučna snaga	Hlađenje	Min./Nom./Max. kW 0,31/0,59/0,72	0,31/0,77/1,05	0,31/1,00/1,40	0,31/1,27/1,50	0,27/1,52/1,74	-/1,85/-	-/2,77/-	
	Grijanje	Min./Nom./Max. kW 0,25/0,64/0,95	0,25/0,75/1,11	0,25/0,94/1,50	0,25/1,24/1,40	0,26/1,46/1,91	-/1,63/-	-/2,21/-	
Hlađenje	Oznaka energetske učinkovitosti	A ⁺⁺ (D->A ⁺⁺⁺)						A (D->A ⁺⁺⁺)	
	Učin Pdesign	kW 2,00	2,50	3,50	4,20	5,00	6,00	7,10	
	SEER	6,50						6,15	5,15
	Godišnja potrošnja energije	kWh/a 108	135	188	226	269	342	483	
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti	A ⁺ (D->A ⁺⁺⁺)						A (D->A ⁺⁺⁺)	
	Učin Pdesign	kW 2,20	2,40	2,60	3,30	3,80	4,80	6,20	
	SCOP/A	4,20						4,10	3,81
	Godišnja potrošnja energije	kWh/a 733	801	867	1.075	1.297	1.654	2.275	

Unutarnja jedinica		FTXF20F	FTXF25F	FTXF35F	FTXF42F	FTXF50F	FTXF60F	FTXF71F	
Dimenzije	Jedinica Visina x Širina x Dubina	mm 286x770x225				mm 295x990x263			
Kvaliteta zraka		Filtar za zrak							
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBa 20/25/33/39	20/26/33/40	20/27/34/43	22/30/36/45	31/34/39/45	33/36/41/45	34/37/42/46
	Grijanje	Tihi/Niski/Srednji/Visoki	dBa 21/28/34/39	21/28/34/40	21/29/35/40	22/28/34/44	30/33/38/44	32/35/40/44	33/36/41/45

Vanjska jedinica		RXF20F	RXF25F	RXF35F	RXF42F	RXF50F	RXF60D9	RXF71D9
Dimenzije	Jedinica Visina x Širina x Dubina	mm 556x740x343				mm 610x923x367		mm 734x870x373
Razina zvučnog tlaka	Hlađenje	Nom./High	dBa -/46		-/48		49/-	52/-
	Grijanje	Nom./High	dBa -/47		-/48	-/49	49/-	52/-
Radno područje	Hlađenje	Okolina	Min.~Max. °CDB -10 ~48					
	Grijanje	Okolina	Min.~Max. °CDB -15 ~24					
Radna tvar	Tip / GWP / Punjenje	kg / TCO,Eq R-32/675/0,42/0,28	R-32/675/0,55/0,37	R-32/675/0,75/0,51	R-32/675/0,80/0,54	R-32/675/1,15/0,78		
Dimenzije priključka	Duljina cijevi	VJ - UJ	Max. m 20				30	
	Visinska razlika	UJ - VJ	Max. m 12				20	
Napajanje	Faza / Preporučeni osigurač (MFA)	A 1~/16				A 1~/20		

* Integrirano u klasu 20-25-35-50. Uključeno s unutarnjom jedinicom za klasu 60-71. Standardni infracrveni bežični daljinski upravljač uključen u isporuku.

Daikin Hrvatska d.o.o.

Strojarska cesta 20, 10 000 Zagreb, Hrvatska | Tel.: + 385 1 60 65 850 | e-mail: office@daikin.hr | www.daikin.hr