

Sensira FTXC

Zidna jedinica | Hlađenje i grijanje



FTXC-E




RXE-E



ARC486A2



uključeno*



Cijene		FTXC20E + RXC20E	FTXC25E + RXC25E	FTXC35E + RXC35E	FTXC50E + RXC50E	FTXC60E + RXC60E	FTXC71E + RXC71E
s PDV-om	Cijena seta (unutarnja + vanjska jedinica)	€ 737,50	800,-	862,50	1.287,50	1.537,50	2.100,-
	Cijena unutarnje jedinice	€ 250,-	262,50	287,50	437,50	512,50	700,-
	Cijena vanjske jedinice	€ 487,50	537,50	575,-	850,-	1.025,-	1.400,-
bez PDV-a	Cijena seta (unutarnja + vanjska jedinica)	€ 590,-	640,-	690,-	1.030,-	1.230,-	1.680,-
	Cijena unutarnje jedinice	€ 200,-	210,-	230,-	350,-	410,-	560,-
	Cijena vanjske jedinice	€ 390,-	430,-	460,-	680,-	820,-	1.120,-

Energetska učinkovitost		FTXC20E + RXC20E	FTXC25E + RXC25E	FTXC35E + RXC35E	FTXC50E + RXC50E	FTXC60E + RXC60E	FTXC71E + RXC71E
Rashladni učin	Min./Rated/Max.	kW 1,3/2,0/3,0	1,3/2,5/3,0	1,3/3,5/4,0	1,4/5,1/6,2	1,8/6,2/7,0	2,3/7,1/7,3
Učin grijanja	Min./Rated/Max.	kW 1,3/2,5/4,0	1,3/2,8/4,0	1,3/4,0/4,8	1,4/5,6/6,6	1,5/6,4/8,0	2,3/8,0/9,0
Prijključna snaga	Hlađenje	Min./Nom./Max. kW 0,30/0,60/1,15	0,30/0,77/1,15	0,32/1,05/1,74	0,30/1,55/2,11	0,38/1,89/2,05	0,44/2,38/2,54
	Grijanje	Min./Nom./Max. kW 0,28/0,67/1,35	0,28/0,75/1,35	0,28/1,07/1,57	0,27/1,52/1,85	0,33/1,68/2,35	0,50/2,46/2,74
Hlađenje	Oznaka energetske učinkovitosti	A++ (D->A+++)					A (D->A+++)
	Učin	Pdesign kW 2,08	2,57	3,44	5,08	6,21	6,96
	SEER	6,89	6,84	6,87	6,45	6,40	5,30
	Godišnja potrošnja energije	kWh/a 106	131	175	276	339	460
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti	A+ (D->A+++)					A (D->A+++)
	Učin	Pdesign kW 1,87	2,23	2,24	3,90	4,10	6,35
	SCOP/A	4,40	4,45	4,28	4,42	4,24	3,81

Unutarnja jedinica				FTXC20E	FTXC25E	FTXC35E	FTXC50E	FTXC60E	FTXC71E
Dimenzije	Jedinica	Visina x Širina x Dubina	mm	288x770x234				297x990x273	
Kvaliteta zraka				Filtar od titanijeva apatita, filter za zrak					
Ventilator - brzina protoka zraka	Hlađenje	Tihi/Niski/Srednji/Visoki	m³/min	5,4/6,1/8,1/10,8		5,4/6,4/8,7/11,1	7,4/8,2/9,9/12,5	10,2/12,5/14,5/20,4	
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBA	21/26/33/40		22/26/34/41	30/33/39/47	31/38/42/48	

Vanjska jedinica				RXC20E	RXC25E	RXC35E	RXC50E	RXC60E	RXC71E
Dimenzije	Jedinica	Visina x Širina x Dubina		mm	550x658x273			615x845x300	695x930x350
Razina zvučnog tlaka	Hlađenje	Visoki		dBA	45		46	51	54
Radno područje	Hlađenje	Okolina	Min.~Max.	°CDB	10~46			-10~46	
	Grijanje	Okolina	Min.~Max.	°CDB	-15~24				
Radna tvar	Tip / GWP / Punjenje		kg / TCO,Eq		R-32/675/0,55/0,371		R-32/675/0,75/0,506	R-32/675/1,00/0,675	R-32/675/1,10/0,743
Dimenzije priključka	Duljina cijevi	VJ - UJ	Max.	m	20			30	
	Sustav	Prednapunjeno		m	8				
	Visinska razlika	UJ - VJ	Max.	m	15			20	
Napajanje	Faza / Preporučeni osigurač (MFA)			A	1~/16				

Standardni infracrveni bežični daljinski upravljač uključen u isporuku.

Daikin Hrvatska d.o.o.

Strojarska cesta 20, 10 000 Zagreb, Hrvatska | Tel.: + 385 1 60 65 850 | e-mail: office@daikin.hr | www.daikin.hr